

21.000N | SlipStop 100

TOTAL MARK | Lamination Films

Features

21.000N | SlipStop 100 is a clear matt textured polypropylene film suitable for indoor use. This product is developed as a short term (anti-slippery) overlamination for floor decals, roll-ups, table and counter top applications. Being a polypropylene, it is an economical and environmental friendly alternative to PVC films. The SlipStop 100 offers a permanent acrylic adhesive, formulated to give exceptional clarity and bond strength. The adhesive will perform impeccably on most common printing inks. In case of specific ink formulations however, we advise to test before use.

In order to achieve a perfect end result, we recommend to combine the SlipStop 100 lamination film with our **40.100N | StrongTack** (permanent) or the **51.101N | StrongTouch** (removable) print film.

21.000N | SlipStop 100 is available in 1370mm & 1524mm (width) x 50m (length) rolls.

Technical & Performance Information

| | |
|------------------------------------|----------------------------------------------|
| Film Thickness | 100 micron |
| Adhesive Thickness | 25 micron |
| Total Thickness | 125 micron |
| Adhesive type | High tack permanent clear waterbased acrylic |
| Release Liner | 140 gsm liner |
| Artificial Weathering * | 1 year |
| Adhesion to steel (20 mins / 180°) | 14 N/25mm |
| Adhesion to steel (24 hrs / 180°) | 22 N/25mm |
| Dimensional Stability | Excellent |
| Application Temperature | +5 to +25 °C |
| Service Temperature | -40 to +95 °C |

* equivalent to vertical exposure in Mid-European climate

Certifications

| | |
|-----------------------|-------|
| Anti-Slip Rating | R9 |
| Indirect Food Contact | 21CFR |

Warranty

iSee2 warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user stores the material in the original boxes (out of direct sunlight) from our factory. We also recommend to store our material at 21°C with 50% relative humidity. iSee2 only warrants our products to be free from defects in workmanship or defects in iSee2 material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise shall be assumed by the seller or manufacturer. User assumes all risk and liability in connection herewith. All data values quoted above are typical and should not be used to deem the product defective, if measured values are different.