

61.115N | Pick n Transfer 115

Features

61.115N | Pick n Transfer is a high tack transparent polypropylene application tape of 115 micron, ensuring easy handling and clean pick up of all brands of vinyl. Pick n Transfer 115 is used to transfer decals and die cut lettering from silicone paper to the final surface of application. The special acrylic modified adhesive guarantees an easy transfer and very easy removal of the application tape. The transparency of the film allows perfect positioning. This tape has a siliconised kraft liner which allows pieces of tape to be cut to shape prior to application.

61.115N | Pick n Transfer is available in 1000mm (width) x 50m (length) rolls.

Technical & Performance Information

Film Thickness	115 micron
Adhesive Thickness	12 micron
Total Thickness	127 micron
Adhesive type	Modified acrylic
Release Liner	80 gsm siliconised kraft - red printed grid liner
Artificial Weathering*	XX
Film Tensile Strength MD	XX
Film Elongation MD	XX
Adhesion to steel (20 mins / 180°)	3 N/25mm
Adhesion to steel (24 hrs / 180°)	Good
Dimensional Stability	<0,5 mm
Application Temperature	+10 to +40°C
Service Temperature	XX

* equivalent to vertical exposure in Mid-European climate

Warranty

iSee2 warrants our material for one (1) year from date of shipment. The shelf life of our material is dependent on storage conditions. We recommend that the end user stores the material in the original boxes (out of direct sunlight) from our factory. We also recommend to store our material at 21°C with 50% relative humidity. iSee2 only warrants our products to be free from defects in workmanship or defects in iSee2 material. We will replace or credit any material deemed defective. No acceptance or responsibility for loss, damage or expense implied or otherwise shall be assumed by the seller or manufacturer. User assumes all risk and liability in connection herewith. All data values quoted above are typical and should not be used to deem the product defective, if measured values are different.